

MERENDA WALLPAPER

merendawallpaper@gmail.com
merendawallpaper.com

646-431-2472

This Design is printed on our
PVC FREE PREPASTED WALLPAPER

IMPORTANT!!

****This Paper comes untrimmed from side to side and Installer must TRIM THE WHITE SELVEDGE EDGE OF PAPER TO MATCH PAPER CORRECTLY!**

Use a straightedge at the end of the printed pattern.

Overlap, Match and double cut on the wall using a double cut tape to protect your wall from being cut.

*****ALWAYS HANG THIS PAPER IN SEQUENCE OFF OF THE ROLL. VARIATION IN COLOR MAY OCCUR THROUGHOUT THE ROLLS.**


Surface Preparation: Walls should be clean, dry, and EVEN IN COLOR. PRIME WALLS WITH A WHITE WALLPAPER PRIMER. Remove any old wallpaper and loose paint. There should be no mold, grease, or dirt present. Roughen painted surfaces with sandpaper. Scrape powdery, flaky surfaces. New plaster should be completely dry. Wall surfaces should be primed and then prep-coated using a latex wallpaper prep coat and allowed to dry completely before beginning installation. We recommend using a Zinnser Shieldz wallpaper. In some cases, or for a superior installation, a liner paper may be recommended. It is at the discretion of your paper hanger whether this step is necessary/recommended for your installation. For superior results, a liner paper is recommended.

A professional paper hanger is recommended to best assess the ideal installation specifications based on your unique environment. For a professional paper hanger in your area please consult the Wallpapers installers Association (WIA) <https://www.wallcoveringinstallers.org/>. We recommend that the paper order quantities, or "roll counts", be carefully calculated. If you are using a professional hanger, they will provide this service. website for further instructions on measuring for wallpaper.

- 1) Inspect material to be hung for imperfections. Examination of the paper before hanging is the buyer's responsibility. If any errors in the aforementioned are found, we ask that you submit the claim for review within two weeks of having received the wallpaper. Once cut, no claims for return may be made. Loosely roll the sheet with the printed side facing in, completely submerge the rolled sheet in the water tray long enough to fully wet the panel and activate the adhesive (10 to 15 seconds).

Remove the roll by pulling the leading edge out of the tray slowly and lay the sheet on the floor glue side up

646-431-2472



MERENDA WALLPAPER

merendawallpaper@gmail.com
merendawallpaper.com

The booked strip will now have graphics on both sides with the glue in contact with it self, the sheet should remain booked for approximately 5 minutes. Unfold the top half of the sheet, leaving the bottom half of the sheet booked.

Tip - if the product is made from natural fiber, it will expand slightly in water, for best results, soak and book each panel the same amount of time.

IMPORTANT Avoid creasing the paper when booking – it is not necessary for the booked panel to lay perfectly flat.

You can also use a sponge with water or a spray bottle with water to activate the paper.

Optionally, you can use a spray bottle filled with clean water, lightly spray the wall (this will assist in ease of movement when positioning).

Align the right-hand side of the first sheet with the straight (vertical) line you have marked using the pencil . Once the sheet is in position lightly smooth the top section of the sheet allowing the rest of the sheet to drop down the wall.

Smooth down the paper with the sponge and smoothing tool, working from top center to bottom edges.

While it is important to use a damp sponge to remove bubbles during the initial application, there's no need to worry about clearing smaller bubbles at this time. After 15 minutes, smooth out any remaining large bubbles using a smoothing tool. Bubbles that are smaller than a 50cent piece will dissipate as the wallpaper sets. Ensure that the edge stays on the pencil mark, use the smoothing tool press firmly along the edge of the wallpaper to 'lock it down'

Please Note: when smoothing do not apply excessive pressure, as you do not want to damaged the product.

Cleaning:

In general, clean surface using a microfiber cloth. Merenda Wallpapers are spot washable with warm water. Do not rub excessively or scrub, as this can cause burnishing or removal of color.

646-431-2472